



PCT/EP 03 / 1 4 9 4 6



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 09 FEB 2004

WIPO

PCT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely adds the company to certain additional company law rules.


Signed

Stephen Hordley

Dated

31 December 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)

PCT/EP 03 / 1 4 9 4 6

30DEC02 E774032-1 D03022
P01/7700 0.00-0230265.1

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

PU 02118

2. Patent application number

(The Patent Office will fill in this part)

0230265.1

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Amersham Biosciences AB
Björkgatan 30
SE 751 85 Uppsala
Sweden

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Sweden

08249120001

4. Title of the invention

Piston and Scraper Assembly

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)ROLLINS, Anthony, John; HAMMER, Catriona, MacLeod and
HAMMETT, Audrey, Grace, Campbell
Amersham plc
Amersham Place
Little Chalfont
Buckinghamshire HP7 9NA

Patents ADP number (if you know it)

0853 0859001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if

Yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d)).

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description	<u>5</u>
Claim(s)	<u>1</u>
Abstract	<u>1</u>
Drawing(s)	<u>3</u>

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

HAMMER, Catriona, MacLeod

Signature 

Date

30 December 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

FRANKS, Barry
01494 542196**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

DUPLICATE

PISTON AND SCRAPER ASSEMBLY

Field of the Invention

The present invention relates to piston and scraper assemblies, for high-pressure
5 chromatography columns, of the type mentioned in the preambles of the independent claims.

Prior Art

In high-pressure chromatographic columns, a piston is often arranged movably in the
chromatography column in order to allow the chromatography medium to be compressed and
10 consolidated by the piston. In this way a substantially homogeneous bed of separation
medium can be obtained. A problem which occurs during compression of the medium is that
abrasive medium particles can become trapped between the sides of the piston and the column
wall. These particles not only damage the cylinder walls but can also damage the piston seals.
US 5169522 describes a high pressure chromatography column with a piston movable in the
15 chromatography cylinder in which the head of the piston is provided with a frit holder which
supports a cylinder wall scraper. The purpose of the scraper is to move packing media ahead
of the piston in order to prevent the packing media from reaching the sealing O-rings on the
piston wall. The scraper is in the form of a ring with an internal thread which co-operates with a
externally threaded portion of the frit holder. A problem with this prior art device is that in
20 order to prevent packing media from passing the scraper, the gap between the scraper and the
cylinder wall must be smaller than the diameter of media particles. This requires very fine,
and expensive, machining tolerances and surface finishes on both the scraper and the cylinder
wall. Additionally, the scraper is unable to prevent the liquid from coming into contact with
the sealing O-rings on the piston wall. This is a problem if the O-rings are not resistant to the
25 liquids used in the column, such as cleaning liquids or process liquids.

Summary of the Invention

According to the present invention, at least some of the problems with the prior art are solved
by means of a piston and scraper assembly having the features present in the characterising
30 part of claim 1.

Brief Description of the Figures

Figure 1 shows a schematically cross-section through a portion of a chromatography column provided with a piston and scraper assembly in accordance with a first embodiment of the present invention;

- 5 Figure 2 shows an enlargement of a portion of the piston and scraper assembly from figure 1; and,

Figure 3 shows an enlargement of a portion of a second embodiment of a piston and scraper in accordance with the present invention.

10 Detailed Description of Embodiments Illustrating the Invention

Figures 1 and 2 show schematically a portion of a chromatography column 1. Column 1 comprises a cylindrical cylinder wall 3 of internal diameter $\varnothing C$. A movable, stepped, cylindrical piston 5 closes one end of column 1. Piston 5 has a front, first face 7 which is intended to face the separation media during use and which is provided with a collecting
15 space 9 for liquid in the column 1. A through hole 11 extends through piston 5 and connects collecting space 9 with a fluid line 13 connectable to the rear, second face 15 of piston 5. First face 7 and a first portion 17 of length $L1$ of piston 5 has a diameter $\varnothing 1$ which is less than the diameter $\varnothing 2$ of second face 15. The diameter $\varnothing 2$ of second face 15 and the remaining length
20 $L2$ of piston 5 is sufficiently less than the internal diameter $\varnothing C$ of cylinder wall 3 so as to allow the piston to move freely up and down column 1. Collecting space 9 is covered by a liquid permeable plate 19 which allows liquid from the inside of the column 1 to flow into the collecting space 5 in the collecting space 9 but which prevents bed media from passing into the collecting space 9.

- 25 Piston 5 has spaced first and second annular grooves 21, resp. 23, provided in its cylindrical surface of diameter $\varnothing 1$. First annular groove 21 is a small distance $d1$ from the first face 7 and second groove 23 further away from the first face at a distance $d2$ from first groove 21. First and second groove 23 are a depth $D1$ mm deep and have a square cross-section. The step 24 in the diameter of the cylindrical piston surface from diameter $\varnothing 1$ to diameter $\varnothing 2$ at distance
30 $L1$ from the first face 7 of the piston is further away from the first face than $d2$.

A scraper 25 is attachable to the first portion 17 of piston 5 and together they form a piston and scraper assembly 26. Scraper 25 is in the form of a ring with an L-shaped cross-section. The base 27 of the L-shaped scraper 25 is intended to extend from the column wall 3 towards the centre of the column far enough that it overlaps plate 19 and thereby can retain plate 19 on piston 5, leaving a central opening of diameter $\emptyset s$. The back 29 of the L-shaped scraper 25 is intended to fit between the in the first portion 17 of the piston and the cylinder wall and extends in the longitudinal direction of the column from the liquid permeable plate 19 towards step 24. The length of back 29 is chosen such that back 29 does not come into contact with step 24 when correctly fitted, as if it was longer this could prevent scraper 25 being correctly fitted onto piston 5 if any foreign material was present on step 24.

Scraper 25 is intended to scrape the cylinder wall 3 and base 27 is provided with a lip 31 on its outer face 33. The diameter of lip 31 is chosen so that it is in scraping contact with cylinder wall 3 when fitted to a piston 5 inside a column 1, so lip 31 may be made of a resilient material and can have an uncompressed diameter which is greater than the internal diameter $\emptyset C$ of cylinder 3. Preferably lip 31 is arranged at join between the outer face 33 and the end face 34 of base 27 which faces away from piston 5. A flange 35 of an outer diameter $\emptyset F$ such that it is in contact with cylinder wall 3 is provided at an intermediate position on back 29. Flange 35 is provided at a position on back 29 which overlaps second groove 23. The outer face 33 tapers inwards from lip 31 to the base of flange 35, leaving a gap 36 between the outer face 33 and the cylinder wall 3.

The inner face 37 of the "back" of the L-shape of scraper 25 has a diameter $\emptyset S$ which is a sliding fit on first portion 17 of piston 5 and is provided with a complementary sealing and locking groove 39 of depth $D2$ mm at a position which is opposite second annular groove 23 when scraper 25 is correctly mounted to piston 5. The inner face 37 is preferably tapered at its end 41 furthest from the base 27 in order to facilitate mounting scraper 25 onto piston 5.

First annular groove 21 contains sealing means such as a sealing ring, e.g. an O-ring 43. The dimensions of O-ring 43 are chosen such that when scraper 25 is correctly mounted then O-ring 43 prevents the passage of liquid and bed media between first portion 17 and scraper 25, thereby preventing the bed media from abrading the wall of the piston and the inner surface of the scraper. Preferably the thickness of O-ring 43 is 10%-50% greater than the depth $D1$.

Preferably the dimensions and elasticity of O-ring 43 are chosen so that it also pushes lip 31 against the cylinder wall 3, thereby preventing liquid and bed media from entering the gap 36 between the outer face 33 and the cylinder wall 3.

5 Second groove 23 contains resilient locking, sealing and biasing means such as a sealing ring, e.g. an O-ring 45. The dimensions of O-ring 45 are chosen such that when scraper 25 is correctly mounted with sealing and locking groove 39 opposite second annular groove 23 then O-ring 45 extends into sealing and locking groove 39 with sufficient force to prevent scraper 25 being pulled off piston 5 during normal use once it has been inserted into column

10 1. Preferably the thickness of O-ring 45 is between 10% and 100% greater than the combined depths $D1 + D2$. O-ring 45 is also dimensioned, and its elasticity chosen, so as to seal between first portion 17 and scraper 25 as well as to push flange 35 with sealing force against cylinder wall 3, thereby preventing media entering between piston 5 and cylinder wall 3.

15 The scraper and piston assembly 26 can be assembled in the following way:

resilient locking, sealing and biasing means 45 is fitted into second groove 23 locking and sealing groove 39;

sealing means 43 are fitted into first groove 21;

plate 19 is positioned on first face 7;

20 scraper 25 is positioned with tapered end 41 against first face 7 and then pushed towards second face 15 of piston 5. As scraper 25 travels towards second face 15 its inner face 37 compresses sealing means 43 and locking, sealing and biasing means 45 until sealing and locking groove 39 on scraper 25 moves to a position opposite second groove 23. At this point resilient locking, sealing and biasing means 45 which had been compressed into second
25 groove 23 by scraper inner face 37 expands into sealing and locking groove 39. This acts as a snap lock to hold scraper 25 onto piston 5.

Outside of the column 1, the piston and scraper assembly 26 is demountable by pulling scraper away from piston 5 – as scraper 25 is not radially constrained it can expand slightly to
30 ease the passage of its inner face 37 over locking, sealing and biasing means 43. However, once the piston and scraper assembly is fitted into column 1 then the scraper is radially constrained by the cylinder wall 3 and it more difficult to pull scraper off piston 5. Preferably the materials used in the manufacture of scraper, piston and locking, sealing and biasing

means 43 and the dimensions chosen for their designs are selected so that during normal use scraper 25 cannot be removed from piston 5 when inside a column 1.

In this way, a scraper and piston assembly is provided which seals reliably, which is easy to assemble but which is secure against unwanted disassembly during use.

A second embodiment of a piston and scraper assembly 26' in accordance with the present invention is shown in figure 3. The same reference numbers are used for features which correspond to the features shown in figures 1 and 2. This piston and scraper assembly 26' is provided with a single groove 23' in the piston 5 which receives a locking, sealing and biasing means 43. This embodiment does not provide such good sealing against liquid coming into contact with locking, sealing and biasing means 43 as the first embodiment of the present invention does, but is cheaper to manufacture. It is more suitable for short duration use, and may be disposed of after a short period of use, as the locking, sealing and biasing means 43 may be attacked by the liquid used in the column and wear out quickly.

Preferably scraper 25 is manufactured from a polymer material which is resistant to the fluids used during running, and cleaning of chromatography columns. Preferably the scraper material is sufficiently elastic for the scraper to be snap-fitted onto the piston. The piston may also be made from a polymer material. Suitable materials are, for example, PEHD and PTFE, optionally reinforced with fibres, e.g. glass fibres or carbon fibres.

While the embodiments of the present invention have been illustrated with examples in which the grooves have square cross-sections, other shaped cross-sections such as rectangular, semi-circular, tapered, etc are naturally also possible. The sealing rings may conceivably have cross-sections which are not round, such as X, V, oval, etc.

The above mentioned embodiments are intended only to illustrate the present invention and are not intended to limit the scope of protection claimed by the following claims.

Claims

1. Piston and scraper assembly (26, 26') comprising a piston (5) and a scraper (25) wherein said piston (5) has a front, first face (7) a cylindrical portion (17) and a second, rear face (15), and is provided with an annular groove (23, 23') of depth D1 mm in the cylindrical portion (17), and wherein the scraper (25) is a ring, adapted to fit onto piston (5), with an L-shaped cross-section and having a complementary groove (39) of depth D2 mm in an inner face (37), characterised in that said annular groove (23, 23') is provided with a resilient sealing, locking and biasing means (45) which extends from said annular groove (23, 23') into said complementary groove (39) in order to retain said scraper (25) on said piston (5).
2. Piston and scraper assembly in accordance with claim 1 characterised in that said piston is provided with a further annular groove (21) containing a sealing means (43).
3. Piston and scraper assembly in accordance with any of the previous claims characterised in that said resilient sealing, locking and biasing means (45) is a sealing-ring with a thickness which is greater than $D1 + D2$ mm.
4. Piston and scraper assembly in accordance with any of claims 2-3 characterised in that said further annular groove (21) is closer than said annular groove (23, 23') to the first, front face of piston (5).
5. Piston and scraper assembly in accordance with any of the previous claims characterised in that said scraper is made of a polymer material.

Abstract

A piston and scraper assembly (26) for a high-pressure liquid chromatography column (1) is provided with a snap lock between the piston (5) and the scraper (25). The snap lock comprises a groove (23) in the piston wall (17), a complementary groove (39) in the inner face of the scraper (25) and a locking, sealing and biasing means such as a resilient O-ring (43) which fits into said grooves.

Fig. 2




Fig. 1




Fig. 2




Fig. 3

PCT Application
PCT/EP2003/014946

